



# Quick Patch Work Wrap

H | CLASS™ 100Q

Finished Size: 80" x 8" (200 x 20 cm)

## SEWING SUPPLIES

- H|CLASS™ 100Q sewing machine by HUSQVARNA VIKING®
- 10-12 different fabric strips in coordinated colors, 2" x 32" (5 x 80 cm)
- Watersoluble stabilizer, 82" x 10" (205 x 25 cm)
- 1/4" (6 mm) wide Steam A Seam II - Fusible fabric adhesive
- Robison Anton 30 wt. rayon embroidery thread in matching color.
- DMC hand embroidery thread: Pearl Cotton Variations, 4 skeins in matching colors to your shawl fabrics.
- Pictogram pen
- Rotary cutter; cutting mat and quilting ruler
- Straight pins

## CUTTING SQUARES

- Cut the fabric strips into 2" (5 cm) square pieces.

## SEWING TIP

Because there will probably be a lot of left over fabrics, gather your friends and all of you can sew a shawl.

## SEWING THE SHAWL

- On the 82" x 10" (205 x 25 cm) water soluble stabilizer measure in 1" (2.5 cm) on one long side and both short ends and draw horizontal and vertical lines 2" (5 cm) apart to create a 2" x 2" (5 x 5 cm) grid.
- Pin the 2" squares randomly over the grid.
- Thread the H|CLASS™ 100Q sewing machine with 30 wt. rayon embroidery thread both in top and in bobbin.
- Attach presser foot B and select stitch I I, a serpentine stitch.
- Sew on the grid lines over each fabric square edge, covering all edges including outside edges. Remove pins as you come to them.
- Dissolve the stabilizer in water.

## ADDING THE FRINGE

- Fuse one side of the Steam a Seam II strips close to the edge of each short end of the shawl. Remove paper.
- Cut the DMC embroidery thread into desired lengths and arrange on top of the Steam A Seam II strip with threads separated.
- Iron the threads to fuse them to the shawl.
- Sew a straight stitch across the threads.
- Cut and trim the fringe to an even length.

